

DE NORA LIDA® CURRENT DISTRIBUTOR

MATERIAL SPECIFICATIONS		
Current Distributor 15mm W x 1mm x 50m		
Width	mm	15
Thickness	mm	1
Cross Section	mm ²	15
Weight	g/m	68
Electrical resistance	Ohm/m	0.037
Current Distributor 10mm W x 0.5mm x 50m		
Width	mm	10
Thickness	mm	0.5
Cross Section	mm ²	5
Weight	g/m	23
Electrical resistance	Ohm/m	0.11
SUBSTRATE COMPOSITION		
ASTM B265 Titanium Grade 1		
Density	Kg/m ³	4511
Melting point	°C	1660
Modules of Elasticity	Mpa	10.2
Tensile Strength	Mpa	240 Min.

The values of materials specifications are nominal.

Milan August, 2015

All information, recommendations and suggestions in this brochure concerning the use of products are based upon tests and data believed to be reliable. Since the actual use by others is beyond control of Industrie De Nora S.p.A no guarantee, expressed or implied, is made by Industrie De Nora S.p.A as to the effect of such use or the results to be obtained, nor does Industrie De Nora S.p.A assume any liability arising out of use by others of the products referred to herein. Nor is the information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. Nothing herein contained is to construed as permission or as a recommendation to infringe any patent.